

External Swage Stems

Male NPT End Tubular Type

Features

- Designed for hose I.D.s 1-1/4" - 10"; ferrule size depends on the hose O.D.. Refer to page 578 to select the correct ferrule
- For higher working pressure applications use long style stems and ferrules

| Hose I.D. | Plated Carbon Steel Part # | 316 Stainless Part # | Long Style Carbon Steel Part # |
|-----------|----------------------------|----------------------|--------------------------------|
| 1-1/4" | TM20 | TMR20 | TML20 |
| 1-1/2" | TM24 | TMR24 | TML24 |
| 2" | TM32 | TMR32 | TML32 |
| 2-1/2" | TM40 | TMR40 | TML40 |
| 3" | TM48 | TMR48 | TML48 |
| 4" | TM64 | TMR64 | TML64 |
| | --- | TMR64-42 | --- |
| 5" | TM80 | --- | TML80 |
| 6" | TM96 | TMR96 | TML96 |
| | --- | TMR96-42 | --- |
| 8" | TM128 | --- | --- |
| 10" | --- | --- | --- |



Beveled End for Welding

| Hose I.D. | Unplated Carbon Steel Part # | 316 Stainless Steel Part # | Long Style Unplated Carbon Steel Part # |
|-----------|------------------------------|----------------------------|---|
| 1-1/4" | TP20 | --- | TPL20 |
| 1-1/2" | TP24 | --- | TPL24 |
| 2" | TP32 | TPR32 | TPL32 |
| 2-1/2" | TP40 | --- | TPL40 |
| 3" | TP48 | TPR48 | TPL48 |
| 4" | TP64 | TPR64 | TPL64 |
| | TP64-42 | --- | TPL64-42 |
| 5" | TP80 | --- | TPL80 |
| 6" | TP96 | --- | TPL96 |
| 8" | TP128 | --- | TPL128 |
| 10" | TP160 | --- | TPL160 |



Grooved End

| Hose I.D. | Plated Carbon Steel Part # | 316 Stainless Part # | Long Style Plated Carbon Steel Part # |
|-----------|----------------------------|----------------------|---------------------------------------|
| 1-1/4" | TG20 | --- | TGL20 |
| 1-1/2" | TG24 | TGR24 | TGL24 |
| 2" | TG32 | TGR32 | TGL32 |
| 2-1/2" | TG40 | TGR40 | --- |
| 3" | TG48 | TGR48 | TGL48 |
| 4" | TG64 | TGR64 | TGL64 |
| | TG64-42 | --- | TGL64-42 |
| 5" | TG80 | --- | --- |
| 6" | TG96 | --- | TGL96 |
| 8" | TG128 | --- | TGL128 |
| 10" | --- | --- | --- |

