

## Air King® Accessories

### Features

- The use of an Air King safety clip or wire type retainer is necessary to ensure couplings will not become accidentally disconnected, this guarantees the fittings are properly connected as the pin will not go through the holes in the mating flanges until couplings are locked in place
- Only one Air King safety clip or wire type retainer is required for each Air King universal coupling
- Sold in package quantities only

### Standard Safety Clip

#### Feature

- Same size clip can be used for all coupling sizes



Wire Diameter	Part #	Pkg Qty
.080"	AC1	25

### Safety Pins

#### Feature

- Heavy duty, oversized



Wire Diameter	Part #
.058"	AKSP1
.091"	AKSP25

### Synthetic Lanyard

#### Features

- Synthetic cord
- Same size for all coupling sizes



Part #	Pkg Qty
ACL8	25

### 2-Lug Washers

#### Features

- 2-lug couplings use the same size washer, part number's AWR4, AWS6
- Neoprene is oil resistant



AWR4



AWS6



#### Specifications

- Rubber temperature range: -20°F to 160°F (-29°C to 71°C)
- Neoprene temperature range: -20°F to 190°F (-29°C to 88°C)

Style	Rubber Part #	Neoprene Part #	Pkg Qty
2 lug	AWR4 <sup>1</sup>	AWS6	50

<sup>1</sup> Made from styrene-butadiene (SBR)

### 4-Lug Washer

#### Feature

- 4-lug couplings use the same size washer, part number AWR14

#### Specifications

- Rubber temperature range: -20°F to 160°F (-29°C to 71°C)



Style	Rubber Part #
4 lug	AWR14

E