

## Long Handle Short Shank Suction Hose Females

**Features:**

- powder coated aluminum swivel nut
- for suction and low pressure discharge only



Female Swivel NST (NH)	Hose Size	Powder Coated Aluminum Part #
4"	4"	<b>LHFS400F</b>
4½"	4"	<b>LHFS4045F</b>

## Angle and Suction Elbows

**Features:**

- for use on pump discharge valves, or suction inlets to minimize hose kinking
- rocker lug swivel
- satin brass finish
- -C polished chrome plated



30° elbow



45° elbow

Male NST (NH) Thread	Female NST (NH) Thread	Angle	Brass Part #
2½"	2½"	30°	<b>RSE30250F-C</b>
		45°	<b>RSE45250F</b>
		45°	<b>RSE45250F-C</b>
		90°	<b>RSE90250F</b>
		90°	<b>RSE90250F-C</b>

## Continuous Swivel Elbows

**Features:**

- allows hose to swing when connected
- full waterway reduces friction loss
- short style radius is 2½" measured from the center of the waterway to the end of the discharge thread



Female NPT Thread	Male Thread	Length	Cast Brass Part #
1½"	1½" NST (NH)	2½"	<b>CSES150F</b>
2"	1½" NST (NH)	2½"	<b>CSES2015F</b>
1½"	1½" NPT	2½"	<b>CSES150T</b>

## Dixon® Angle and Suction Elbows N54

**Features:**

- ideal for fire apparatus with front suction connections
- anodized, powder coated aluminum, extruded
- anodized female swivel connections



90° elbow

Male NST (NH) Thread	Female NST (NH) Swivel Thread	Angle	Aluminum Part #
2½"	2½"	30°	<b>N5430-25F25F</b>
		45°	<b>N5445-25F25F</b>
		60°	<b>N5460-25F25F</b>
		90°	<b>N5490-25F25F</b>

- Replacement washers can be found on page 785