



Flat Seal Coupling Assemblies

Application:

- Designed for use on lay flat hose and single jacket fire hose with a wall thickness between 5/64" and 3/16".

Features:

- Flat seal couplings are for use with flat seal clamps only.
- brass swivel nut on complete assembly and female assemblies
- maximum recommended torque 40 ft/lbs
- Torque values for clamps are based on dry bolts. The use of lubricants on bolts will adversely effect clamp performance. 



complete assembly



female Flat Seal
NPSM



male Flat Seal
NPSM



male Flat Seal
NPT

Complete Flat Seal Assembly - NPSM

Size	Aluminum Part #	Price/E ¹
1½"	FS150	\$209.00
2½"	FS250	312.00

Female Flat Seal Assembly - NPSM

Size	Aluminum Part #	Price/E ¹
1½"	FSF150	\$168.00
2½"	FSF250	253.00

Male Flat Seal Assembly - NPSM

Size	Aluminum Part #	Price/E ¹
1½"	FSM150	\$131.00
2½"	FSM250	206.00

Complete Flat Seal Assembly - NST (NH)

Size	Aluminum Part #	Price/E ¹
1½"	FS150F	\$209.00
2½"	FS250F	312.00

Female Flat Seal Assembly - NST (NH)

Size	Aluminum Part #	Price/E ¹
1½"	FSF150F	\$168.00
2½"	FSF250F	253.00

Male Flat Seal Assembly - NST (NH)

Size	Aluminum Part #	Price/E ¹
1½"	FSM150F	\$131.00
2½"	FSM250F	206.00

Male Flat Seal Assembly - NPT

Size	Aluminum Part #	Price/E ¹
1½"	FSM150T	\$131.00
2"	FSM200T	158.00
2½"	FSM250T	206.00

¹ price includes clamps

Flat Seal Gaskets



Size	Buna Part #	Price/E
1½"	FSG150	\$1.35
2"	FSG200	1.45
2½"	FSG250	1.45
3"	FSG300	2.00
4"	FSG400	2.25