




The Right Connection®

Fueler 100™ Automatic Diesel Nozzle

Designed for high volume fuel transfer



For use with: Gasoline up to 25% Ethanol blend and Diesel / Bio Diesel up to 20% (B20)



Applications:

- Designed for high volume fuel transfer, typical uses include high volume truck fleet and bus terminals, fuel oil delivery and industrial operations

Materials:

- Body: high strength, durable aluminum casting
- Spout: aluminum
- Stem packing: Teflon™, eliminates leaks
- Spout lock nut: nylon, does not gall
- Seals: Viton™ / Nitrile, cold climate seals are available
- Poppet disc: Viton™
- Lever: high strength aluminum casting
- Packing: Teflon™
- Vacuum cap: Zinc
- Body cap: cast aluminum
- Main stem: stainless steel


Features:

- Heavy duty, high flow automatic nozzle
- Roto-matic latch pin provides smoother auto shut off, grooved spout holds nozzle in the tank
- Dual poppets provides easy high pressure operation making it easy to change the spout
- 1 3/8" spout
- Handguard: integrated with body
- Weight: 6.9 lbs.
- Length: 13.5"
- Can be rebuilt
- Individually boxed and packed 7 per carton, 49 lbs. per carton

Specifications:

- Inlet: 1 1/2" or 1 1/4" NPT or BSPP
- Hold open clip: two speed
- Working pressure: **50 PSI** maximum

Replacement Parts



Key	Part Number	Description
1	SF1N	spout assembly
2	050B	diaphragm assembly
3	117AS	poppet assembly
4	116	lever with pad
5	125	body

Dixon Bayco

800 High Street • Chestertown, MD 21620
 phone: 410.778.2000 • fax: 410.778.4702
dixonvalve.com

Dixon Group Canada Limited

2315 Bowman Street • Innisfil, Ontario L9S 3V6
 phone: 800.355.1991 • fax: 877.436.6251
canada.dixonvalve.com

